

CS99-107
Serial number 09/413,177

Please amend claim 13 as follows:

02
13. (Amended) The method of claim 1 wherein an insulating layer is deposited over said inductor thereby encapsulating said inductor.

Claims 19-21: Please cancel claims 19-21.

03
22. (Amended) The method of claim 1, said first layer of disposable solid and said second layer of disposable solid comprising nitride.

REMARKS

Examiner P. Brock II is thanked for the thorough examination of the Prior Art, Examiner is also thanked for the indication of allowing claims 3, 4 and 7 if these claims are rewritten in independent form including all of the limitations of the base claim and any intervening claims.

Favorable reconsideration of this application in light of the above amendments and the following remarks is respectfully requested.

The invention teaches new method for creating an inductor on the surface of a silicon substrate. The invention provides overlying layers of oxide fins beneath a metal inductor. The oxide fins provide the stability support for the overlying metal inductor while also allowing horizontal air columns to simultaneously exist underneath the inductor. Overlying layers of air cavities that are spatially inserted between the created overlying layers of oxide fins can be created under the invention by repetitive application of the mask used. The presence of the air wells on the surface of the substrate significantly reduces parasitic capacitances and series resistance of the inductor associated with the substrate.

The invention specifically provides for a method of forming air gaps within an integrated circuit structure, comprising:

- forming a structure for a first layer of cavities
- forming a structure for a second layer of cavities above and aligned with the structure for the first layer of cavities
- creating a first and a second layer of cavities, and
- forming a metal inductor overlying the created cavities.

CS99-107
Serial number 09/413,177

Election/Restrictions

The Examiner's Final Election and Restriction requirement is acknowledged. Non-elected claims 19-21 have been cancelled, a divisional application will be filed at a later date.

Claim Rejections under 35 U.S.C. 112

Reconsideration of the rejection of claims 1-8 and 22 under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention is respectfully requested based on the following.

The Examiner is thanked for pointing out the various problems in the claims. The claims have been carefully reviewed and amended to correct those problems the Examiner pointed out, in addition to others. All claims are now believed to be in allowable condition.

Specifically, claim 1 has been amended as kindly suggested by Examiner.

CS99-107

Serial number 09/413,177

Claim 2 has been amended so that the term "metal layer" has been uniformly used in this claim.

The term "a disposable solid" has been replaced with the term "disposable solid" as kindly suggested by Examiner.

In claims 3 and 4, the terms "a first layer of disposable solid" and "a second layer of disposable solid" have been replaced with the terms "said first layer of disposable solid" and "said second layer of disposable solid".

In light of the foregoing response, applicant respectfully requests that the Examiner's rejection of claims 1-8 and 22 under 35 U.S.C. 112, second paragraph, be withdrawn.

Claim rejections - 35 U.S.C. § 103

Reconsideration of the rejection of claims 1, 2, 5, 6, 15-17 under 35 U.S.C 103 as being unpatentable over Lur et al. (US Patent 5,413,962) in view of Staudinger et al. (US Patent 5,481,131) is respectfully requested based on the following.

Lur et al. (US Patent 5,413,962) provides for a multi-level electrode metal structure and the interconnecting inter-level

metal studs used in the fabrication of VLSI circuits, in this respect therefore, Lur et al.:

- does not provide for creating a high quality inductor on the surface of a silicon semiconductor substrate as claimed in claims 1, 15-18, 20 of the instant invention
- does not provide for an dielectric of air that surrounds interconnect metal
- does not provide for a number of overlying air gaps that are interconnected as claimed in claims 1 and 3-5 of the instant invention
- Lur et al. does not provide for oxide fins (36, 38, Fig. 13 of the instant invention) underneath the metal inductor 44; the oxide fins of the instant invention provide support and stability for the overlying metal 44, simultaneously allowing horizontal air columns to exist underneath the inductor
- Lur et al. does not create an inductor (44, Fig. 13 of the instant invention) that overlies a upper layer of dielectric as claimed in claims 1 of the instant invention
- Lur et al. does not provide for openings (22, 24, 32 and 34, Fig. 13 of the instant invention) in layers of dielectric through which nitride or any other disposable material can be removed as claimed in claims 3, 4, 5 of the instant invention

- Lur et al. does not provide for overlying layers of disposable material, such as nitride, interspersed with layers of dielectric as claimed in claims 1 and 3-5 of the instant invention
- the final construct that is provided by Lur et al. does not comprise horizontal air gaps (36, 38, Fig. 11 of the instant invention) between which horizontal layers of a dielectric are created, see Fig. 11 of the instant invention, and
- Lur et al. shows interconnect studs that connect to bit lines and word lines of what appears to be a DRAM circuit configuration; gate electrodes are provided by Lur et al.; the instant invention is silent on this aspect of the Lur invention and is not limited to a DRAM device or the use of gate electrodes.

Regarding claims 1, 2 and 5 the following applies:

- the metal layer that is created by Lur et al., layer 26, Fig. 1, is connected to a source/drain region or to a gate electrode; the metal layer of the instant invention, layer 12, is not limited to being connected to a gate electrode
- the first layers of interconnect metal, layers 40, Fig. 1, that are created by Lur et al. connect to interconnect plugs

26; the instant invention does not create these first layers of interconnect metal

- Lur et al. deposits a number of thin envelop oxide layers such as layer 42, Fig. 1, layer 42, Fig. 2, layer 42, Fig. 4, layer 42, Fig. 6, layer 42, Fig. 8, layer 42, Fig. 9, layer 42, Fig. 10; all envelop layers have been referred to by the number "42" by Lur et al., the multiplicity of layers has been deposited for the figures that have been referenced; the instant invention does not make use of such thin layers of oxide for protective purposes of the interconnect metal
- applicant respectfully disagrees with Examiner regarding the statement that Lur et al. creates, Figs. 2-4, a structure for a first layer of cavities; Lur et al. does not make use of cavities but in contrast etches away the inter-level dielectric (col. 3, line 62) leaving an air dielectric 85, Fig. 11 Lur et al.) between the electrode metal layers; an similar comment applies to Examiner's contention that Lur et al. creates a first and a second layer of cavities: the (only) cavity that is created by Lur et al. is cavity 85, shown in Fig. 11 where col. 3, lines 61 e.a.): "the inter-level dielectric is etched away". After the inter-level has been etched away, a (col. 3, lines 63 e.a.) "the surface of all electrode pattern metal and interlevel stud metal is covered with a coating of thin envelop oxide". Lur et al.

provides an etch for the removal of the inter-level dielectric, which may be considered a standard procedure. Lur et al, therefore does not provide for the creation of overlying layers of disposable solid, nor for the creation of access holes through layers of dielectric nor for the removal of the disposable solid through these access holes, nor for creating (as the instant invention does) overlying and interconnected air cavities.

Staudinger et al. provides for an Integrated Circuit having passive circuit elements but at no time does Staudinger et al. provide for the essential aspects of the instant invention that have been summarized supra, that is:

- forming a structure for a first layer of cavities
- forming a structure for a second layer of cavities above and aligned with the structure for the first layer of cavities,
- creating a first and a second layer of cavities, and
- forming a metal inductor overlying the created cavities.

Regarding claims 15, 16, while many inductors are created having a spiral shape, not all inductors have a spiral shape. Since the inductor of the invention is created on the surface of a layer of dielectric, layer 42, Fig. 12, the inductor of the

invention is not limited to a spiral shape but can also be circular or polygonal in shape. This is specified in claims 15-17.

Regarding claims 17, the inductor 44 of the invention is created having very low parasitic capacitance between the inductor 44, Fig. 13, and a metal layer 12, Fig. 13. For this reason the inductor 44 can be created having a high inductive value and can at the same time be used for high frequency applications. In other words: by providing the invention it is now possible in the context of the instant invention to create a high (inductive and Q) value, high frequency inductor. The layer or layers of material underlying the inductor is key and of the essence to these performance characteristics of the inductor. It must therefore be recognized and specified that, if an inductor is created using the instant invention, this inductor can be a high inductive value, high frequency performance inductor as claimed in claim 18. Without this claim it would not be clear just what could be accomplished using the invention.

The above arguments can be summarized by stating that it would not be obvious to combine the teachings of Lur et al. with those Staudiner, since there is no suggestion or motivation in the teachings of any of the patents of the present invention.

These inventions no not provide for the creation of horizontal air gaps that are interspersed with layers of dielectric while further these inventions do not provide for a method of removal of a disposable solid, such as nitride, for the creation of the air gaps as claimed in claims 1, 2, 5, 6 and 15-17 of the instant invention.

None of the applied or known references address the invention as shown in the amended claims in which air gaps are created between overlying layers of dielectric. The invention is believed to be patentable over the prior art cited, as it is respectfully suggested that the combination of these various references cannot be made without reference to Applicant's own invention. None of the applied references address the problem of creating a high inductive value, high frequency inductor overlying a layer of metal.

Applicant has claimed his process in detail. The processes of Figs. 1-11 are believed to be both novel and patentable over these various references, because there is not sufficient basis for concluding that the combination of claimed elements would have been obvious to one skilled in the art. That is to say, there must be something in the prior art or line of reasoning to

CS99-107

Serial number 09/413,177

suggest that the combination of these various references is desirable. We believe that there is no such basis for the combination. We therefore respectfully request Examiner P. Brock II to reconsider his rejection in view of these arguments and the amendments to the Claims.

In light of the foregoing response, applicant respectfully requests that the Examiner's rejection of claims 1, 2, 5, 6, 15-17 under 35 U.S.C 103 as being unpatentable over Lur et al. (US Patent 5,413,962) in view of Staudinger et al. (US Patent 5,481,131), be withdrawn.

Claim rejections - 35 U.S.C. § 103

Reconsideration of the rejection of claims 8-12 under 35 U.S.C 103 as being unpatentable over Lur et al. (US Patent 5,413,962) and Staudinger (US Patent 5,481,131) as applied to claim 1 above in view of Havemann et al. (US Patent 5,481,131) is respectfully requested based on the following.

The relative merits of Lur et al. and Staudinger with respect to claim 1 have been discussed above and are enclosed at this time by reference.

With respect to claim 8, Havemann et al. (U.S. Patent 5,668,398) does not cite, contrary to Examiner's assertion, in the text referred to by Examiner, that is col. 5, lines 49-67 and col. 6, lines 15-25 a disposable solid that comprises a polymer. In the text that is referred to, the word "polymer" does not appear. In addition, the text referred to by examiner and as referred to above, does not, again contrary to Examiner's assertion, describe Figs. 5c and 5d but describes Figs. 1d through 3.

It is, in view of the above highlighted discrepancies between the Examiner's references and the specification provided by Havemann, difficult to provide a meaningful argument in response to Examiner's assertions. It may however be pointed out that the mere fact of a layer of polymer being applied by a prior art invention does not by itself lead to the conclusion that this prior art application can be used to there-from derive the instant invention. The instant invention provides a novel method of applying and at a later time in the process of removing a (patterned layer of) disposable solid, the invention is completely different from the Havemann et al, invention. Claim 8 specifies that a polymer can be used for a first and second layer of disposable solid and does thereby not provide

any link or basis of commonality with the Havemann et al. invention.

Would it, for instance, be reasonable to conclude that, because the tires of a bicycle and the tires of a car contain air, that therefore the car is identical to the bicycle or that the car can be created based on the design or the procedure that is used to build the bicycle?

With regard to claim 9, Havemann et al. teaches, col. 5, lines 49-67, that "the disposable solid layer 18 is removed through the porous dielectric layer 20 to form air gaps 22 as shown in Fig. 1E. This latter process is performed by "exposing the wafer to oxygen or oxygen plasma, the oxygen moves through the porous dielectric layer 20 to reach the disposable solid layer 18 and react with the solid layer 18 and convert it to a gas that moves back out of the porous dielectric 20."

Claim 9 specifies creating a first and a second layer of cavities is heating the substrate in oxygen, evaporating the disposable solid layer using O₂ plasma. This claim 9 however is a dependent claim to claim 1, which specifies, among others: "forming a structure for a first layer of cavities over the thin layer of oxide and aligned with the metal layer, the forming a

structure for a first layer of cavities comprising applying and patterning a first layer of disposable solid **followed by** applying and patterning a first layer of oxide, the patterning a first layer of oxide further comprising forming a first and a second opening through the first layer of oxide.

From the above quote it is clear that the invention directly, by creating openings through the first layer of oxide, provides a path for the removal of the disposable solid. Havemann does not provide for this but removes a solid through a more cumbersome process that has been detailed above and that, in view of the method applied by Havemann et al., does not lead to as direct and as thorough a removal of the solid as is provided by the instant invention, whereby the removable solid can be directly attacked by oxygen resulting in evaporating the disposable solid layer using O₂ plasma. This process is easier to apply, more effective and provides more dependable (better removal of the disposable solid) results in creation an air filled space in the surrounding layer.

With regards to claim 10, this claim teaches creating a first and a second layer of cavities is introducing a solvent to the substrate, dissolving the polymer (that is used as a disposable solid).

Applicant has carefully reviewed the text cited by Examiner in Havemann et al. invention with respect to claim 10, that is col. 5, lines 49-67 and col. 6, lines 15-25, but is, contrary to Examiner's assertion, not able to locate any reference to the introduction of a solvent to the substrate. In addition, the referred to text of the Havemann et al. invention describes Figs. 1D through 2 and not, as asserted by Examiner, Figs. 5c and 5d.

Regarding claim 11, Havemann in the description of Figs. 5A through 5D, to which Examiner refers, the description of which is provided by Havemann in Col. 6, lines 43-76 and col. 7, lines 1-11 and not, as asserted by Examiner, in col. 5, lines 49-67, does provide for cavities between patterned layers of metal. First, Fig. 5A, patterned and overlying layers 16/28 of metal and second oxide are created over first oxide layer 14. A disposable solid 18, Fig. 5B, is deposited, a porous dielectric 20 is deposited over the disposable solid 18 after which the disposable solid 18 is evaporated through the porous layer 20 of dielectric, creating cavities 22, Fig. 5D, between adjacent layers of metal traces and there-over deposited layers 24 of second oxide.

Claim 11 of the instant invention specifies heating the substrate to evaporate the polymer, thereby creating a first and a second layer of cavities. These layers of cavities are clearly shown in the cross sections of Fig. 11, elements 36 and 38. These cavities are not between patterned layers of metal and oxide but are created as an interconnected structure 36/38 within the dielectric layer 30, the interconnects being openings 22 and 24. This interconnected structure cannot, in its creation or in its final cross section, be compared with the openings 22, Fig. 5D of Havemann for the reason that neither the creation nor the cross section have any commonality. The air gaps of the instant invention and the air gaps provided by Havemann et al. are created by removing a disposable solid, an opening is defined by the removable solid after which the removable is removed. Not in common between Havemann et al. and the instant invention are, among others, the process of the creation of the patterned layers of disposable solid, the cross sections of the created layers of disposable solid, the manner in which the disposable solid is removed, the layers that are adjacent to the created layers of disposable solid and the final structure, of which the air cavities form a part.

Havemann et al. does not, contrary to Examiner's assertion, provide for a first and a second layer of cavities, Havemann

creates one layer of cavities surrounded by metal interconnects and overlying patterned layers of oxide.

Regarding claim 12, which specifies creating a first and a second layer of cavities by applying a vacuum to the substrate, dissolving the polymer, the invention provided by Havemann does not provided for this method in essence because Havemann does not provide openings 32/34 and 22/24, Fig. 11 of the instant invention, through which the disposable solid is directly accessible and through which the disposable solid can therefore directly be removed. Havemann et al. would, in applying as vacuum to the substrate, most likely destroy the porous layer 20, Fig. 5C, overlying the created air gaps.

While applicant acknowledges the teachings of Lur, Staudinger and Havermann et al. as cited by the Examiner, and although applicant does not necessarily agree that the Examiner's arguments show sufficient and proper basis for suggestion or motivation to modify or combine Lur, Staudinger and Havermann et al., applicant nonetheless also asserts that there is absent within the portions of Lur, Staudinger and Havermann et al. or any combination thereof, as cited by the Examiner, an express or inherent teaching of each and every

limitation within applicant's invention as taught and claimed within claims 8-12 of the instant invention.

Claims 8-12 are dependent claims to claim 1, neither Lur or Staudinger nor Havermann et al. nor any combination thereof provide for the aspects of the instant invention that are specified in independent claim 1 of the invention on which claims 8-12 are based.

Specifically provided by the instant invention, aspects that are not provided by Lur nor Staudinger nor Havermann et al. or any combination thereof, are:

- forming a structure for a first layer of cavities over a thin layer of oxide and aligned with a metal layer, by applying and patterning a first layer of disposable solid followed by applying and patterning a first layer of oxide, thereby forming a first and a second opening through the first layer of oxide
- forming a structure for a second layer of cavities above and aligned with the structure for the first layer of cavities by applying and patterning a second layer of disposable solid followed by applying and patterning a second layer of oxide thereby forming a first and a second opening through the second layer of oxide

- creating the first and the second layer of cavities
- performing an oxide deposition over the second layer of cavities, creating a thin layer of oxide, and
- forming a metal inductor on the thin layer of oxide.

To combine the teachings of Lur and Staudinger and Havermann et al. is not obvious, since there is no suggestion or motivation in the teachings of any of these patents of the present invention. The instant invention specifically provides a method of forming air gaps within an integrated circuit structure and of forming a metal inductor on an upper thin layer of oxide. In the context of the instant invention, and not either supported by or inferred by or referred to by Lur and Staudinger and Havermann et al. singly or in combination thereof, provides a first and second layer of cavities, the cavities interconnected with openings, the second layer of cavities exposed through openings for easy and complete removal of a created patterned layer of a disposable solid, over the surface of a substrate.

In light of the foregoing response, applicant respectfully requests that the Examiner's rejection of claims 8-12 under 35 U.S.C 103, be withdrawn.

Claim rejections - 35 U.S.C. § 103

Reconsideration of the rejection of claims 13 and 18 under 35 U.S.C 103 as being unpatentable over Lur et al. (US Patent 5,413,962) and Staudinger as applied to claim 1 above in view of Abidi et al. (US Patent 5,481,131) is respectfully requested based on the following.

The relative merits of Lur et al. (US Patent 5,413,962) and Staudinger (US Patent 5,481,131) relating to claim 1 have been discussed above and are enclosed at this time by reference.

Regarding claim 13, it is clear that an insulation layer, as specified by Abidi et al., can be used for multiple applications. In the case of the instant invention, the insulation layer is specified and provided in order to provide a more rugged construction that is protected from environmental impact during subsequent processing cycles. Without this protective layer the inductor of the invention would be exposed and unprotected, resulting in a device that is prone to environmental damage.

Abidi et al. creates an inductor over a pit in a substrate and essentially shows the inductor as having a spiral shape.

Other shapes are highlighted by Abidi et al., which however does not provide any commonality between Abidi et al. and the instant invention. The essence of the instant invention is the creation of air gaps interspersed with layers of dielectric, Abidi does not address these aspects of the instant invention. It must again be pointed out that, since the inductor of the instant invention is created overlying the surface of a layer of dielectric, this inductor is not in any way limited to the shape in which this inductor can be created. For this reason the various shapes in which an inductor can be created must be specified in order to avoid incompleteness of the specification or the claims.

Regarding claim 18, the inductor of the invention is created having very low parasitic capacitance between the inductor 44, Fig. 13, and a metal layer 12, Fig. 13. For this reason the inductor can be created having a high inductive value and can at the same time be used for high frequency applications. In other words: by providing the invention it is now possible in the context of the instant invention to create a high value, high frequency inductor. The layer of material underlying the inductor is key and of the essence to these performance characteristics of the inductor. It must therefore be recognized and specified that, if an inductor is created

using the instant invention, this inductor can be a high inductive value, high frequency performance inductor as claimed in claim 18. Without this claim it would not be clear just what could be accomplished using the invention.

The above arguments can be summarized by stating that it would not be obvious to combine the teachings of Lur et al. with those of Chu et al. and Abili et al., since there is no suggestion or motivation in the teachings of any of the patents of the present invention.

None of these inventions provide for the creation of horizontal air gaps that are interspersed with layers of dielectric while further none of these inventions provide for a method of removal of a disposable solid, such as nitride, for the creation of the air gaps as claimed in the claims of the instant invention. None of the applied or known references address the invention as shown in the amended claims in which air gaps are created between overlying layers of dielectric.

The invention is believed to be patentable over the prior art cited, as it is respectfully suggested that the combination of these various references cannot be made without reference to Applicant's own invention.

None of the applied references address the problem of creating a high inductive value, high frequency inductor overlying a layer of metal. Applicant has claimed his process in detail. The processes of Figs. 1-11 are believed to be both novel and patentable over these various references, because there is not sufficient basis for concluding that the combination of claimed elements would have been obvious to one skilled in the art.

That is to say, there must be something in the prior art or line of reasoning to suggest that the combination of these various references is desirable. We believe that there is no such basis for the combination. We therefore respectfully request Examiner P. Brock II to reconsider his rejection in view of these arguments and the amendments to the Claims.

In light of the foregoing response, applicant respectfully requests that the Examiner's rejection of claims 13 and 18 under 35 U.S.C 103, be withdrawn.

Claim rejections - 35 U.S.C. § 103

Reconsideration of the rejection of claim 14 under 35 U.S.C 103 as being unpatentable over Lur et al. (US Patent 5,413,962) and Staudinger as applied to claim 1 above in further in view of One of ordinary skill in the art.

The relative merits of Lur et al. (US Patent 5,413,962) and Staudinger (US Patent 5,481,131) relating to claim 1 have been discussed above and are enclosed at this time by reference.

Claim 14 specifies that the partially fabricated integrated circuit structure comprising transistors being bipolar or CMOS devices interconnected to form an RF amplifier.

This aspect of the instant invention is not implied without the specific identification there-of as provided in claim 14. It has been stated previously that, by providing the invention it is now possible in the context of the instant invention to create a high value, high frequency inductor.

Such an inductor, having high inductive and high Q values is most suited for application as a high frequency inductor for high-end performance devices. Such devices however can be created for a number of different applications, one of the preferred applications of the invention is that the inductor,

CS99-107

Serial number 09/413,177

created by the invention, as applied in combination with CMOS devices whereby these CMOS devices more specifically are interconnected to form an RF amplifier.

Claim 14, which is a dependent claim to claim 1, therefore limits the invention to a specific application, which represents an important market segment of semiconductor devices and which therefore requires to be specifically identified.

In light of the foregoing response, applicant respectfully requests that the Examiner's rejection of claim 14 under 35 U.S.C 103, be withdrawn.

Claim rejections - 35 U.S.C. § 103

Reconsideration of the rejection of claim 14 under 35 U.S.C 103 as being unpatentable over Lur et al. (US Patent 5,413,962) and Staudinger as applied to claim 1 above in further in view of One of ordinary skill in the art.

Other Considerations

No new independent claims have been written as a result of this office action.

SUMMARY

The invention teaches new method for creating an inductor on the surface of a silicon substrate. The invention provides overlying layers of oxide fins beneath a metal inductor. The oxide fins provide the stability support for the overlying metal inductor while also allowing horizontal air columns to simultaneously exist underneath the inductor. Overlying layers of air cavities that are spatially inserted between the created overlying layers of oxide fins can be created under the invention by repetitive application of the mask used. The presence of the air wells on the surface of the substrate significantly reduces parasitic capacitances and series resistance of the inductor associated with the substrate.

It is requested that should Examiner not find the claims to be allowable that he call the undersigned Attorney at his convenience at 845-452-5863 to overcome any problems preventing allowance.

Attached hereto is a marked-up version of the changes made to the specification and claims by the current amendment. The attached page is captioned:

CS99-107

Serial number 09/413,177

"Version with markings to show changes made."

Respectfully submitted,

A handwritten signature in black ink, appearing to be 'S. Ackerman', with a stylized loop and a long horizontal stroke extending to the right.

Stephen B. Ackerman (Reg. No 37,761)

Version with markings to show changes made

Please amend the claims as follows.

1. (Thrice Amended) A method of forming air gaps within an integrated circuit structure, comprising the steps of:

providing a partially fabricated integrated circuit structure and depositing a layer of dielectric thereon;

forming a metal layer on [the surface of] said dielectric layer;

depositing a thin layer of oxide over [the surface of] said dielectric layer, thereby including said metal layer;

forming a structure for a first layer of cavities over [the surface of] said thin layer of oxide and aligned with said metal layer, said forming a structure for a first layer of cavities comprising applying and patterning a first layer of [a] disposable solid followed by applying and patterning a first layer of oxide, said [forming a structure for] patterning a first layer of [cavities] oxide further comprising forming a first and a second opening through said first layer of oxide;

forming a structure for a second layer of cavities above and aligned with said structure for said first layer of cavities, said forming a structure for a second layer of cavities comprising applying and patterning a second layer of

[a] disposable solid followed by applying and patterning a second layer of oxide, said [forming a structure for] patterning a second layer of [cavities] oxide further comprising forming a first and a second opening through said second layer of oxide; creating the first and the second layer of cavities; performing an oxide deposition over [the surface of] said second layer of cavities, creating a thin layer of oxide; and forming a metal inductor on [the surface of] said thin layer of oxide.

Please amend claim 2 as follows:

2. (Twice Amended) The method of claim 1, wherein said forming a metal layer on [the surface of] said dielectric layer is forming a metal layer [of metal] that has [the] a cross section of a square or a rectangle with essentially vertical sides, whereby [the] a height of said metal layer is equal to [the] a thickness of a conventional semiconductor metal layer, whereby a width of said metal layer is equal to or exceeds its height [by a measurable amount].

Please amend claim 3 as follows:

3. (Thrice Amended) The method of claim 1 wherein said forming the structure for a first layer of cavities comprises the steps of:

depositing [a] said first layer of [a] disposable solid over [the surface of] said thin layer of oxide;

creating an opening in said first layer of [a] disposable solid, whereby said opening aligns with said metal layer and has a dimension when measured in a direction along [the surface of] said thin layer of oxide that is smaller than a dimension of [the surface of] said metal layer [by a measurable amount];

depositing a first layer of oxide over [the surface of] said first layer of [a] disposable solid, thereby including said opening in said first layer of [a] disposable solid, whereby said first layer of oxide has a dimension of thickness in addition to having a dimension of width; and

creating a first and a second opening in said first layer of oxide, whereby said first and second openings are located at [the] opposite extremities of said first layer of oxide, whereby [the] a distance between [the] a [central axis] center of said first and second openings is less than said dimension of width of said first layer of oxide [by a measurable amount].

Please amend claim 4 as follows:

4. (Thrice Amended) The method of claim 1 wherein said forming the structure for a second layer of cavities comprises the steps of:

depositing [a] said second layer of [a] disposable solid over [the surface of] said first layer of oxide, thereby including said first and second openings created in said first layer of oxide;

creating an opening in said second layer of [a] disposable solid, whereby said opening aligns with said metal layer and has a dimension when measured in a direction along [the surface of] said first layer of oxide that is approximately equal to a dimension of the opening created in said first layer of [a] disposable solid;

depositing a second layer of oxide over [the surface of] said second layer of [a] disposable solid, thereby including said opening created in said second layer of [a] disposable solid, whereby said second layer of oxide has a dimension of thickness in addition to having a dimension of width; and

creating a first and a second opening in said second layer of oxide, whereby said first and second openings are located at opposite extremities of said second layer of oxide, whereby a distance between a [central axis] center of said first and second openings is less than said dimension of width of said second layer of oxide [by a measurable amount].

Please amend claim 5 as follows:

5. (Thrice Amended) The method of claim 1, said creating a first and a second layer of cavities is removing said first and second layer of [a] disposable solid, said removal to take place by accessing said first and second layer of [a] disposable solid by means of said first and second opening created in said second layer of oxide, furthermore by accessing said first layer of [a] disposable solid by means of said first and second openings in said first layer of oxide, creating a first layer and a second layer of dielectric comprising horizontal oxide fins, further creating a first layer and a second layer of horizontal air gaps being interspersed with said first layer and a second layer of dielectric.

Please amend claim 6 as follows:

6. (Amended) The method of claim 1 wherein said performing an oxide deposition over [the surface of] said second layer of cavities is creating a thin layer of oxide over [the surface of] said second layer of oxide, thereby furthermore closing [off] said first and said second openings created in said second layer of oxide.

Please amend claim 7 as follows:

7. (Thrice Amended) The method of claim 1, creating additional layers of cavities over a preceding layer of cavities, said additional layers being created prior to performing an oxide deposition over [the surface of] an upper or last layer of cavities, said creation of additional layers of cavities comprising the steps of:

depositing an additional layer of [a] disposable solid over [the surface of] a layer of oxide of a preceding layer of cavities, thereby including first and second openings created in said layer of oxide of a preceding layer of cavities;

creating an opening in said additional layer of [a] disposable solid, said opening being aligned with said metal layer and having a dimension when measured in a direction along [the surface of] said layer of oxide of a preceding layer of cavities that is approximately equal to a dimension of an opening created in a preceding layer of [a] disposable solid;

depositing an additional layer of oxide over [the surface of] said additional layer of [a] disposable solid, thereby including said opening created in said additional layer of [a] disposable solid, said additional layer of oxide having a dimension of thickness in addition to having a dimension of width; and

creating a first and a second opening in said additional layer of oxide, said first and second openings being located at opposite extremes of said additional layer of oxide, a distance between a [central axis] center of said first and second openings being less than said dimension of width of said additional layer of oxide [by a measurable amount], creating a first layer and a second layer of dielectric comprising horizontal oxide fins, further creating a first layer and a second layer of horizontal air gaps being interspersed with said first layer and a second layer of dielectric.

Please amend claim 8 as follows:

8. (Twice Amended) The method of claim 1, said first and second layers of [a] disposable solid comprising a polymer.

Please amend claim 13 as follows:

13. (Amended) The method of claim 1 wherein an insulating layer is deposited over [the surface of] said inductor thereby encapsulating said inductor.

Claims 19-21: Please cancel claims 19-21.

CS99-107

Serial number 09/413,177

22. (Amended) The method of claim 1, said first layer of [a] disposable solid and said second layer of [a] disposable solid comprising nitride.